



Gemineye™
CAMERA SYSTEMS



CAMERA SYSTEMS

Beacons | Lightbars | Minibars | Directional LEDs | Worklamps | Back-Up Alarms

CAMERAS



EC2014-C



EC2014-WC



C2000



C2001



C2002

approvals	IP69K, ECE R10, E13, FCC, CE, C-Tick	IP69K, ECE R10, FCC, CE, RoHS, C-Tick	IP68, E13, FCC, CE	IP68, E13, FCC, CE	IP68, E13, FCC, CE
color	Yes	Yes	Yes	Yes	Yes
power consumption (W)	3	.25	2	2.5	1.5
microphone	Yes	Yes	Yes	Yes	Yes
day / night light sensor	Yes	Yes	Yes	Yes	Yes
dimensions	2.87" x 2.99" x 2.60"	2.87" x 2.99" x 2.98"	3.62" x 3.19" x 2.41"	4.47" x 3.82" x 2.59"	3.03" x 2.47" x 1.99"
weight	0.74 lbs	0.89 lbs	0.9 lbs	1.3 lbs	0.47 lbs
temperature	-22 to +158	-20 to +158	-22 to +149	-22 to +149	-22 to +149
lens angle	120°	120°	110°	110°	110°
lens size	1/3"	1/3"	1/4"	1/4"	1/4"
infrared LEDs	11	11	18	18	9
mechanical vibration	10G	10G	8G	8G	8G
4 pin camera connection	Yes*	Wireless	Yes*	-	Yes*
6 pin camera connection	-	-	-	Yes	-

*threaded connection



Gemineye™
CAMERA SYSTEMS



CAMERA SYSTEMS

Beacons | Lightbars | Minibars | Directional LEDs | Worklamps | Back-Up Alarms

CAMERAS



C2004



C2010



C2011



C2013B

approvals	IP68, E13, FCC, CE	IP68, E13, FCC, CE	IP68, E13, FCC, CE	IP69K, FCC, CE, RoHS
color	Yes	Yes	Yes	Yes
power consumption (W)	1.2	1.5	1.2	1
microphone	-	Yes	-	-
day / night light sensor	-	Yes	-	Yes
dimensions	1.22" x 1.06" x 1.83"	2.68" x 1.34"	1.42" x 1.77"	2.92" x 3.01" x 2.62"
weight	0.22 lbs	0.36 lbs	0.44 lbs	0.6 lbs
temperature	-22 to +149	-22 to +158	-22 to +158	-22 to +158
lens angle	150°	110°	150°	120°
lens size	1/4"	1/4"	1/4"	1/4"
infrared LEDs	-	9	-	18
mechanical vibration	-	10G	-	6G
4 pin camera connection	Yes	Yes*	Yes	Yes*
6 pin camera connection	-	-	-	-

*threaded connection